# **SILVERLINK 600**



DF4/N - Lincat Silverlink 600 Natural Gas Countertop Single Tank Fryer - 2 Baskets - W 450 mm - 11.3 kW The Silverlink 600 Gas Single Tank
Counter Top Fryer delivers 25kg of
chips per hour, while it also features a
twin basket operation which gives you
the flexibility of cooking different foods
or loads simultaneously.

- Single tank fryer with twin basket operation giving you the flexibility to cook different foods or loads simultaneously, delivering 25kg of chips per hour
- Front mounted controls for safety
- Thermostatically controlled to give accurate cooking temperatures throughout cooking. Flame failure device and top temperature cut out ensures safe operation.
- Cool zone collects cooking debris gives cleaner cooking results and saves money by prolonging the life of the oil

- Piezo ignition for easy lighting
- Heavy duty nickel plated baskets for the most demanding of operations
- Front drain off tap for easy removal of cooking oil

### **Specifications**

Summary		Power and Performance	
Brand	Lincat	BTU per Hour	38,555
Range	Silverlink 600	Total Power kW	11.3
Power Type	Gas	Temperature Range °C	110-190
Gas Type	Natural Gas	Temperature Control	Mechanical
Unit Type	Counter-top		
Available in UK Only	No		
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
GTIN	5056105104605		
Key Specifications		Capacity	
Number of Baskets	2	Product Output per Hour	16kg chips - 12mm [frozen], 25kg chips
Number of Tanks	1	r roudet Output per riour	12mm [chi
Gravity Filtration	No	Capacity Litres	8.0
Pumped Filtration	No		
Drain Location	Front-mounted		
Weights and Dimensions		Supply Connections	
Unit Heimbt (Eutemen) nom	/45	Demoise a la stallation	V

Weights and Dimensions		Supply Connections	
Unit Height (External) mm	415	Requires Installation	Yes
Unit Width (External) mm	450	Requires Electrical Supply	No
Unit Depth (External) mm	654	Gas Connection BSP	1/2"
Net Weight Kg	30.9	Gas Consumption at full rate Natural m³ per Hour	1.08
		Gas Pressure Natural mbar	16.2
		Total heat input at full rate Natural kW	11.3
		Total heat input at full rate Natural BTU per hour	38,600





## Shipping

Packed Weight Kg43.2Packed Height cm63.5Packed Width cm70Packed Depth cm55

#### **Available Accessories**

CH01 Caterflex Hose 1/2" - 1 Metre - for use with units up to 66,000 BTU


CH02 Caterflex Hose 1/2" - 1.5 Metre - for use with units up to 56,000 BTU


CN4 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 450 mm


DC01 DONUT CONV KIT DF4/GAS

**SLS4** Lincat Silverlink 600 Free-standing Floor Stand - for units W 450 mm

## **Technical Picture**













**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

\_ .....

**Company No:** 2175448

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm



Product Code: DF4/N Page Number: 3 Print Date: 11/12/2020