

Oracle

THE PRODUCT LINE



ORAC1



ORAC2

STANDARD ELECTRIC CONFIGURATION

Models	Power	Cooking chamber dimensions (L x D x Hmm)	Capacity (Litres)	Electrical power (kW)	Consumption (A)	Microwave (kW)	Impingement (kW)	External dimensions (L x D x Hmm)	Power supply voltage
ORAC1		312x312x178	17,2	3,68	16	1,00	3,00	358 x 743 x 578	1N AC 230V - 50 Hz
ORAC2		312x312x178	17,2	5,95	16	2,00	3,00	358 x 743 x 578	3N AC 400V - 50 Hz

OPTIONAL ELECTRIC CONFIGURATION - REQUEST WHEN ORDERING

Models	Power	Cooking chamber dimensions (L x D x Hmm)	Capacity (Litres)	Electrical power (kW)	Consumption (A)	Microwave (kW)	Impingement (kW)	External dimensions (L x D x Hmm)	Power supply voltage
ORAC1		312x312x178	17,2	3,60	18,2	1,00	3,00	358 x 743 x 578	1N AC 208V - 60 Hz 1N AC 240V - 60 Hz
ORAC1		312x312x178	17,2	2,45	13	1,00	3,00	358 x 743 x 578	1N AC 230V - 50 Hz 1N AC 240V - 50 Hz
ORAC1		312x312x178	17,2	3,25	15	1,00	3,00	358 x 743 x 578	1N AC 230V - 50 Hz 1N AC 240V - 50 Hz
ORAC2		312x312x178	17,2	5,95	28,6	2,00	3,00	358 x 743 x 578	1N AC 208V - 60 Hz 1N AC 240V - 60 Hz
ORAC2		312x312x178	17,2	5,95	28,6	2,00	3,00	358 x 743 x 578	1N AC 208V - 50 Hz 1N AC 240V - 50 Hz

FEATURES

COOKING METHODS

- Impingement with power up to 3 kW.
- Convection with temperature from 95°C to 270°C.
- Microwave with power up to 2 kW.
- Microwave defrost function.
- Manual up to 4 cycles.
- Programmable with the ability to store 1200 cooking programmes in automatic sequence (up to 4 cycles), assigning a name and dedicated icon.

OPERATION

- HD True-Touch™ 7" fully customisable touch screen display.
- Automatic pre-heating.

CLEANING AND MAINTENANCE

- Approved detergents can be used directly on the smooth door surface.
- Removable, non-stick cooking chamber lining for easy cleaning.
- Magnetic air filters can be cleaned in one go.
- Rapid cooling for fast cleaning at end of day.

CONTROL MECHANISMS

- Silent function: the fan speed automatically adjusts based on the operating mode.
- Reminder to clean air filters.
- Standard supply Wi-Fi/Ethernet connection to update software and upload/download cooking programmes.
- Standard supply USB connection to update software and upload/download cooking programmes.

CONSTRUCTION

- External stainless steel finish.
- Front control panel in painted finish.
- Stainless steel oven chamber with bevelled edges.
- Built-in catalytic converter for hood-free use.
- Pull-down door with ergonomic handle.
- When open, the door slides under the cooking surface of the oven, allowing the food to be removed safely without the risk of burns.
- IPX3 protection against water splashes.

CE IPX 3



Oracle

ACCESSORIES



COOKING PLATE

Smooth (included) or ribbed (optional) for guaranteed perfect cooking, browning, toasting.



TEFLON TRAYS

Non-stick, smooth or ribbed trays perfect for browning and toasting food.



STONE PLATE

Handy for cooking and browning bread, pizzas, and flat breads.



ALUMINIUM PEEL

Handy for removing products from the oven chamber. Ideal for sandwiches and pizzas.



NON-STICK LINING KIT

For quick and easy cleaning.



DETERGENTS

Detergents and specific products for easy residue removal and protection of oven surfaces.



UPPER SHELF REST

Shelf with closed sides for storing accessories.



REAR COVER PANEL

Cover panel conceals power cable and air vents. Ideal for open view installations.



STAND

Stand with bottom shelf for one or two ORACLE ovens, with adjustable feet or on wheels.