

LINDA CURVED GLASS



TECHNICAL CHARACTERISTICS

- Display with evaporator
- Working top in stainless steel
- Stainless steel tube structure
- Interior coating in stainless steel AISI 304 18/8
- Side panels and storage doors coated in PVC w/ isolation obtained by injection of high-density polyurethane
- Multi-flexible external and internal corners of 90° and 45° LACE / LSCE and LACI / LSCI
- Plasticised grills display
- Frontal straight glass
- Exposition of stainless steel AISI 304 18/8
- Supplementary 10 Amp plug
- Exterior in skinplate (available in several colors)
- Built-in adjustable feet in height
- Capillary tube expansion valve
- Automatic evaporation
- Digital thermostat for temperature adjustment
- Door magnetic gask and easy to replace.

OPTIONS

- Display with ventilated refrigeration
- External revetment in brushed stainless steel AISI 304
- Stainless steel grills • Acrylic sliding doors for back of the display (except in the model with small glasses)
- Several decorations available.

MOD	COD	↗	📦	💧	🚪	🌡️	💡	❄️
VLC 105	VLC105200	950mm	0,63	131	1	+3/+6	2x8	286
VLC 120	VLC120200	1100mm	0,73	152	1	+3/+6	2x12	473
VLC 150	VLC150200	1400mm	0,93	193	1	+3/+6	2x16	473
VLC 200	VLC200200	1900mm	1,27	262	2	+3/+6	2x20	473
VLC 250	VLC250200	2400mm	1,60	331	2	+3/+6	4x12	800
VLC 300	VLC300200	2900mm	1,94	400	3	+3/+6	4x16	800
VLC CEN 90°	VLCCE9200	900x900mm	0,62	-	-	-	12	-
VLC CEN 45°	VLCCE4200	638x910mm	0,31	-	-	-	12	-
VLC CIN 90°	VLCCI9200	1251x1251mm	0,78	-	-	-	12	-
VLC CIN 45°	VLCCI4200	884x910mm	0,50	-	-	-	12	-
VLC XT	VLCXT200	550mm	-	-	-	-	-	-

Espessura do lateral 45mm | Lateral thickness 45mm | Epaisseur de latéral 45mm | Espesor del lateral 45 mm.



Side view

