



F79/010 - IMC WasteStation Macerator and Dewaterer - with Airbreak

- A solution for your business process up to 700 kg waste per hour, the equivalent of 1450 covers
- Transport savings reduce waste collection costs by up to 80% by reducing the food waste volume and weight requiring collection
- Storage savings by reducing the waste volume, on site waste storage facility requirements are also reduced
- Labour savings reduce staff time processing and managing waste, fast efficient disposal of food waste as and when you need to, with no schedule
- Self-cleaning operation WasteStation can undertake a thorough clean, ensuring the whole system is free of food and grease

Reliable, efficient, safe and easy to operate, the WasteStation allows operators to quickly and effectively remove waste, creating a safer and cleaner kitchen.

- Self-emptying eliminates the need for staff to empty the auger assembly, reducing labour times required to operate the machine.
  Intelligent electronic sensor detects when the bin is full
- Visual control panel kitchens are a noisy environment, so WasteStation incorporates a simple LED display to allow monitoring of the state of the equipment during operation
- Energy savings compact design and short processing times ensure low operating costs and minimal use of kitchen floor space
- Maximise kitchen hygiene fully enclosed system prevents food entering the unit, keeping the machine clean and free of waste, and reducing operational noise. Following each operation, the machine undertakes a quick selfrinse cycle, preventing any build-up of food

With airbreak

# **Specifications**

#### Summary **Power and Performance** Brand Total Power kW 4.1 IMC ΗP Range WasteStation 1.5 Power Type IP Rating IP55 Electric **Operating Decibels** 83 Unit Type Free-standing Available in UK Only No **UK Warranty** 2 Years Parts and Labour Warranty Export Warranty Contact your local dealer Mounting Free-standing GTIN 5056105197034 **Key Specifications** Capacity

WRAS Approved	WRAS Compliant	Type of Waste	Tough waste
Airbreak	Yes	Covers Per Sitting	1450
Manual or Auger Feed	Manual	Capacity Kg per Hour	700
Self Cleaning	Yes		





Weights and Dimensions		Supply Connections	Supply Connections	
Unit Height (External) mm	1000	Requires Installation	Yes	
Unit Width (External) mm	900	Requires Electrical Supply	Yes	
Unit Depth (External) mm	700	UK 3 Pin Plug	No	
Net Weight Kg	192	16A Commando Plug	No	
		Requires Hardwiring	Yes	
		Electrical Supply Rating Watts	4,100	
		Three Phase Amps	8.62	
		Three Phase Voltage	380-415	
		Water Supplied From	Mains Fed	
		Water Connection Pressure Bar	Head of water not less than 0.18 bar	
		Drain Connection	2" waste drain	
		Water Connection	3/4" BSP	
		Water Consumption Litres/min	12	

## Shipping

Packed Weight Kg	211.2
Packed Height cm	152
Packed Width cm	90
Packed Depth cm	115

Available Accessories	
A13/125	Waste Scraper for WasteStation
K12/357	Waste Caddy for WasteStation and WastePro II

# Lincat fift

### Lincat Limited

Whisby Road, Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500 Email: care@lincat.co.uk

### **Export Customers**

Tel: +44 1522 875536

Email: export@lincat.co.uk

Monday – Friday:

8.30am - 5pm

**Opening Hours**