



F79/100 - IMC WasteStation Macerator and Dewaterer - without Airbreak

- A solution for your business process up to 700 kg waste per hour, the equivalent of 1450 covers
- Transport savings reduce waste collection costs by up to 80% by reducing the food waste volume and weight requiring collection
- Storage savings by reducing the waste volume, on site waste storage facility requirements are also reduced
- Labour savings reduce staff time processing and managing waste, fast efficient disposal of food waste as and when you need to, with no schedule
- Self-cleaning operation WasteStation can undertake a thorough clean, ensuring the whole system is free of food and grease

Reliable, efficient, safe and easy to operate, the WasteStation allows operators to quickly and effectively remove waste, creating a safer and cleaner kitchen.

- Self-emptying eliminates the need for staff to empty the auger assembly, reducing labour times required to operate the machine. Intelligent electronic sensor detects when the bin is full
- Visual control panel kitchens are a noisy environment, so WasteStation incorporates a simple LED display to allow monitoring of the state of the equipment during operation
- Energy savings compact design and short processing times ensure low operating costs and minimal use of kitchen floor space
- Maximise kitchen hygiene fully enclosed system prevents food entering the unit, keeping the machine clean and free of waste, and reducing operational noise. Following each operation, the machine undertakes a quick selfrinse cycle, preventing any build-up of food

Specifications

Summary		Power and Performance	9
Brand	IMC	Total Power kW	4.1
Range	WasteStation	HP	1.5
Power Type	Electric	IP Rating	IP55
Unit Type	Free-standing	Operating Decibels	83
Available in UK Only	No		
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
Mounting	Free-standing		
GTIN	5056105197041		
Key Specifications		Capacity	
WRAS Approved	No	Type of Waste	Tough waste

Airbreak Manual or Auger Feed Self Cleaning No No Manual Yes

Covers Per Sitting Capacity Kg per Hour Tough wast 1450 700





Weights and Dimensions		Supply Connections		
Unit Height (External) mm	1000	Requires Installation	Yes	
Unit Width (External) mm	900	Requires Electrical Supply	Yes	
Unit Depth (External) mm	700	UK 3 Pin Plug	No	
Net Weight Kg	280	16A Commando Plug	No	
		Requires Hardwiring	Yes	
		Electrical Supply Rating Watts	4,100	
		Three Phase Amps	8.62	
		Three Phase Voltage	380-415	
		Water Supplied From	Mains Fed	
		Water Connection Pressure Bar	Head of water not less than 0.18 bar	
		Drain Connection	2" waste drain	
		Water Connection	3/4" BSP	
		Water Consumption Litres/min	12	

Shipping

Packed Weight Kg	308
Packed Height cm	0
Packed Width cm	0
Packed Depth cm	0

Available Accessories		
A13/125	Waste Scraper for WasteStation	
K12/357	Waste Caddy for WasteStation and WastePro II	

Lincat fift

Lincat Limited

Whisby Road, Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500 Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Monday – Friday:

8.30am - 5pm

Opening Hours