



**D SERIES TECNOCOMBI GAS COMBI OVEN, DIRECT STEAM, ELECTRONIC CONTROL, 10XGN1/1 TRAYS, CORE PROBE, PROGRAMMABLE, AUTOMATIC WASHING**

---

954342 - GOM10DSL

---

## SPECIFICATIONS

The professional combi ovens of the Tecnocombi line combine tradition and technology in a mix perfect for the chef who looks for advanced and reliable, simple and precise, efficient and robust cooking tools.

They are available with both digital and manual control.

### Why Tecnocombi

Tecnocombi is the cooking solution for the chef that requires the maximum personal control of the cooking parameters and excellent results.

Tecnocombi is recommended for:

Cooking centers, also important for the number of meals served at each service  
Restaurants, trattorias and cafeterias  
Gastronomy, butcher shops or other retail stores that offer cooked food of their own production

### The 2019 renewed line

Born in 2011, they kept all their promises, becoming one of Tecnoinox's best sellers.

Today they are redesigned by Marc Sadler to meet the need for innovation in cooking and usability that we have gathered while conversing with chefs from all over the world.

## Tecnocombi D Series - Digital Professional Combi Ovens

### EXTREMELY EASY TO USE

The Tecnoinox ovens are all designed to be intuitive and easy to use, both in the digital versions and in the manual/electromechanical versions.

The control panels on the digital ovens are equipped with a high visibility colour LCD-TFT display so that recipes and cooking steps are easy to view.

The control panels are equipped with two alphanumeric displays: one for temperature control and one for time or the temperature detected by the core probe.

The capacitive light touch controls and handy push & scroll dial speed up the select and confirm process.

The Tecnocombi digital ovens can manage up to 300 recipes in total, including preset recipes and customised recipes entered by the chef.

Recipes can be found quickly by filtering by recipe name, personal recipes, recent and favourite recipes.

The recipes are real programs that manage up to 8 cooking steps, including automatic preheating.

Important: all cooking parameters can be changed during the cooking process.

### PLAY BUTTON

The play button lights up in different colours to show the status of the oven.

### GREAT PERFORMANCE AND RELIABILITY

### COOKING

The digital ovens work with convection (50-265°C), steam (60-120°C), with a combi cycle (60-250°C) and with automatic preheating.

The preheating temperature is the temperature of the first cooking step in the recipe.

The Tecnocombi digital ovens work with direct steam. The boiler is only provided in versions with 20 trays.

In the combi cycle you can manage up to 19 humidity levels at 5% intervals from 0% to 90%.

The Tecnocombi digital ovens are equipped with a programmable initial steam puff, which can be set to last up to 20 seconds.

### FLEXIBLE

The cooking parameters can even be changed while running the recipe.

## ROBUST

Sealed chamber in AISI 304 stainless steel. Silicone rubber door seal, resistant to heat and ageing, built into the oven front.

## UNIFORM COOKING

Uniform cooking is guaranteed thanks to:

The deflector, designed for the best heat distribution in the chamber.

The professional fans are governed by an inverter, work with 4 speeds and stop instantly when rotation is reversed and the door is opened.

Well-spaced grills, with 70 mm spacing in the Tecnocombi and 85 mm in the Tecnobake.

## SAVE TIME

### STRAIGHT UP TO TEMPERATURE

The power of the heating elements and the gas burners enables the chosen temperature to be reached in just a few minutes.

### PERFECT HYGIENE FAST

The ovens' 3 WASH LEVELS ensure perfect hygiene depending on the level of intensity required.

They are fast and effective: the short cycle lasts just 33 minutes and the intensive cycle at most 77 minutes. EXTRA: a rinse cycle that lasts 7 minutes.

## MORE...

### EXTRAS

#### MANUAL STEAM PUFF

#### HANDLE

Easy-open handle.

#### SOUS-VIDE

Socket for sous-vide skewer probe.

#### DRAIN PROTECTIVE DEVICES

Steam condensation for drain protective devices.

#### USB PORT

Useful for recovering HACCP data recorded during cooking.

### OPTIONS

Reverse door opening

bases with tray racks

hoods

stacking kits (only for electric ovens)  
trays  
external spray gun.

## TECHNICAL DATA

Total Power	<b>19 + 0,5 kW</b>	Fan Speed	<b>4</b>
Gas Power	<b>19 kW</b>	CE Certificate Nr. (Gas Appliance)	<b>CE-0085CP0593</b>
EL Power	<b>0,5 kW</b>	Foot high	<b>65 mm</b>
Frequency	<b>50/60 Hz</b>	Foot adjustment	<b>65/75 mm</b>
Voltage	<b>220-240 1~ V</b>	IPX	<b>4</b>
Fan Motor Power Rating	<b>0,5 kW</b>	Width	<b>86 cm</b>
Nominal Heating Output	<b>19 kW</b>	Depth	<b>71 cm</b>
Trays capacity	<b>10xGN1/1 n°</b>	Height	<b>102 cm</b>
Max. food Load	<b>50 Kg</b>	Packaging Width	<b>93 cm</b>
Natural Gas Consumption	<b>2,01 m³/h</b>	Packaging Depth	<b>85 cm</b>
Oven Chamber Dimensions (WxDxH)	<b>59x37,5x77 cm</b>	Packaging Height	<b>126 cm</b>
Runners	<b>10 n°</b>	Net Weight	<b>129 kg</b>
Distance between shelves	<b>7 cm</b>	Gross Weight	<b>143,2 kg</b>
Timer	<b>0-540 min</b>	Volume	<b>0,99 m³</b>
Oven Version	<b>GN/ electronic</b>		

## ACCESSORIES

- 091910: GN1/1 STAINLESS STEEL BAKING GRID FOR POULTRY
- 091946: STAINLESS STEEL MESH BASKET FOR PRE-FRIED FOOD
- 091947: TEFLON COATED ALUMINUM SPECIAL GRID FOR VEGETABLES
- 091949: STAINLESS STEEL BAKING GRID FOR SKEWERS
- 091950: ALUMINUM TEFLON COATED SPECIAL GRID FOR MEAT AND FISH
- 091951: ALUMINUM TEFLON COATED TRAY FOR EGGS AND OMELETTES
- 091952: ALUMINUM SMOOTH TEFLON COATED TRAY H=20MM
- 091953: ALUMINUM SMOOTH TEFLON COATED TRAY H=40MM
- 091954: ALUMINUM SMOOTH TEFLON COATED TRAY H 65MM
- 9032: GN1/1 STAINLESS STEEL SMOOTH BAKING TRAY H=20MM
- 9033: GN1/1 STAINLESS STEEL SMOOTH BAKING TRAY H=40MM
- 9034: GN1/1 SMOOTH STAINLESS STEEL BAKING TRAY H=65MM
- 9055: GN1/1 STAINLESS STEEL GRID

- 9056: GN1/1 PERFORATED STAINLESS STEEL BAKING H=20MM
- 9057: GN1/1 PERFORATED STAINLESS STEEL BAKING TRAY H=40MM
- 9058: GN1/1 PERFORATED STAINLESS STEEL BAKING TRAY H=65MM
- 9059: GN1/1 ENAMELLED BACKING TRAY H=20MM
- 9060: GN1/1 ENAMELLED BACKING TRAY H=40MM
- 951912: EXTERNAL SHOWER
- 951915: ALKALINE DETERGENT TANK 10LT FOR OVENS
- 951917: ALUMINUM TRAY WITH HEAT RETENTION FOR PIZZA GN1/1
- 951933: ALUMINUM SMOOTH TEFLON COATED TRAY WITH HEAT RETENTION
- 951934: ALUMINUM RIBBED TEFLON COATED TRAY WITH HEAT RETENTION
- 951935: DRAUGHT DIVERTER FOR TECNOCOMBI GAS OVENS
- 951938: CLOSED CABINET WITH SIDE RUNNERS AND DETERGENT TANK SUPPORT FOR GN1/1 OVENS - 7 TRAYS CROSSWISE
- 951939: CROSSWISE HOT CLOSED CABINET, SIDE RUNNERS FOR GN1/1 OVENS - 7 TRAYS CROSSWISE
- 951950: NEEDLE CORE PROBE FOR SOUSVIDE COOKING
- 951953: TEFLON COATED ALUMINUM TRAY GN1/1
- 951954: PREFORATED TEFLON COATED ALUMINUM TRAY GN1/1
- 951961: PIPING KIT FOR WATER INLET AND OUTLET
- 951971: CONDENSATING EXTRACTOR HOOD FOR 6 GN1/1 AND 10 GN1/1 TECNOCOMBI, 230V, 50/60HZ, 0.19KW MOTOR
- 951972: COVERING PANEL FOR TECNOCOMBI OVENS WITH HOOD ON BASE, CUPBOARD, HOT CUPBOARD OR HUMIFIED CUPBOARD
- 951974: BASE FOR 6 AND 10 GN1/1 TRAYS TECNOCOMBI OVENS
- 951976: BASE WITH SIDE RUNNERS FOR 6 AND 10 GN1/1 TRAYS TECNOCOMBI OVENS
- 951981: STACKING ELEMENT FOR 6 AND 10 GN1/1 TRAYS TECNOCOMBI OVENS ON 5 TRAYS BLAST FREEZERS
- 951983: WHEELS KIT FOR OVENS BASE